

Параметры мачты

Тип	Модель	Полная высота мачты (вилы на грунте, мачта установлена вертикально), мм						Максимальная высота подъема (с грузовой решеткой), мм				Высота свободного подъема с грузовой решеткой, мм							Угол наклона мачты α/β, град.				
		2–2,5 т	3 т	3,5 т	4–5 т	5–7 т	10 т	2–2,5 т	3–3,5 т	4–5 т	5–7 т	2–2,5 т	3 т	3,5 т	3,5 т	4–5 т	5–7 т	10 т	2–2,5 т	3–3,5 т	4–5 т	5–7 т	10 т
Двухсекционная мачта без свободного хода	M200	2000	1500	1570	1620	–	–	–	3100	3217	–	–	150	155	160	–	–	–	6/12	6/12	–	–	–
	M250	2500	1750	1820	1870	2030	2230	–	3600	3717	3820	3900	150	155	160	150	165	–	6/12	6/12	6/12	6/12	–
	M300	3000	2000	2070	2120	2280	2480	2850	4100	4217	4320	4400	150	155	160	150	165	140	6/12	6/12	6/12	6/12	6/12
	M350	3500	2250	2320	2370	2530	2730	3100	4600	4717	4820	4900	150	155	160	150	165	140	6/12	6/12	6/12	6/12	6/12
	M400	4000	2550	2620	2670	2830	3030	3400	5100	5217	5320	5400	150	155	160	150	165	140	6/6	6/6	6/12	6/12	6/12
	M450	4500	2800	2870	2920	3080	3280	3650	5600	5717	5820	5900	150	155	160	150	165	140	6/6	6/6	6/12	6/12	6/6
	M500	5000	3050	3120	3170	3330	3530	3900	6100	6217	6320	6400	150	155	160	150	165	140	6/6	6/6	6/6	6/6	6/6
	M550	5500	3350	3420	3470	3630	3830	4200	6600	6717	6820	6900	150	155	160	150	165	140	3/6	3/6	6/6	6/6	3/6
	M600	6000	3600	3670	3720	3880	4080	4450	7100	7217	7320	7400	150	155	160	150	165	140	3/6	3/6	6/6	6/6	3/6
Двухсекционная мачта со свободным подъемом	F200	2000	1500	1570	1620	–	–	–	3100	3217	–	–	496	388	443	–	–	–	6/12	6/12	–	–	–
	F250	2500	1750	1820	1870	2030	2230	–	3600	3717	3820	3880	746	638	693	750	880	–	6/12	6/12	6/12	6/12	–
	F300	3000	2000	2070	2120	2280	2480	2850	4100	4217	4320	4380	996	888	943	1000	1130	1470	6/12	6/12	6/12	6/12	6/12
	F350	3500	2250	2320	2370	2530	2730	3100	4600	4717	4820	4880	1246	1138	1193	1250	1380	1720	6/12	6/12	6/12	6/12	6/12
	F400	4000	2550	2620	2670	2780	3030	3350	5100	5217	5320	5380	1546	1438	1493	1500	1680	1970	6/6	6/6	6/12	6/12	6/12
	F450	4500	–	–	–	–	–	3650	–	–	–	–	–	–	–	–	–	2220	–	–	–	–	6/6
	F500	5000	–	–	–	–	–	3900	–	–	–	–	–	–	–	–	–	2470	–	–	–	–	6/6
	F550	5500	–	–	–	–	–	4200	–	–	–	–	–	–	–	–	–	2720	–	–	–	–	3/6
	F600	6000	–	–	–	–	–	4450	–	–	–	–	–	–	–	–	–	2970	–	–	–	–	3/6
Трехсекционная мачта со свободным подъемом	T360	3600	1800	1870	1870	2030	2335	–	4700	4817	4890	4990	796	688	693	750	985	–	6/6	6/6	6/6	6/6	–
	T400	4000	1950	2020	2020	2170	2470	2700	5100	5217	5310	5390	946	838	843	890	1120	1325	6/6	6/6	6/6	6/6	6/12
	T450	4500	2100	2170	2170	2330	2635	2870	5600	5717	5810	5886	1096	988	993	1050	1285	1495	6/6	6/6	6/6	6/6	6/12
	T500	5000	2300	2370	2370	2530	2805	3035	6100	6217	6305	6400	1296	1188	1193	1250	1460	1660	6/6	6/6	6/6	6/6	6/6
	T540	5400	2400	2470	2470	2665	2940	3225	6500	6617	6710	6800	1396	1288	1293	1385	1590	1850	3/6	3/6	6/6	6/6	3/6
	T600	6000	2600	2670	2670	2900	3140	3425	7100	7217	7310	7400	1596	1488	1493	1620	1790	2050	3/6	3/6	6/6	6/6	3/6
	T650	6500	2800	2870	2870	3075	3405	–	7600	7717	7810	7900	1796	1688	1693	1795	2055	–	3/3	3/3	6/6	6/6	–
	T700	7000	2975	3045	3045	3265	3515	–	8100	8217	8340	8400	1971	1863	1868	1985	2165	–	3/3	3/3	6/6	6/6	–